



Guillemen/DSP Couplings & Adaptors

A French hose coupling system (16 Bar)



Description

This is a two claw symmetrical hermaphrodite connection system. The connection size is determined by the DN size and recognised by its ka lug distance. There are two systems - Gullemin and DSP, which are both interchangeable but are used in different applications.

Options & Material

DN 20 DN 25 DN 40 DN 50

Light Alloy and Brass as standard, Stainless Steel and Gun Metal available upon request.

Caps

Blanking Caps are available with keep chains as standard and can be supplied with or without locking ring.

Washers and Spanners

NBR washers for all DN sizes. A universal Spanner for connecting couplings DN20-DN120

Guillemin

DN Size	Lug Size (ka)	Hose Tail Size (mm)	BSP Male	BSP Female
20	32mm	25mm	¾"	¾"
25	37.5mm	X	1"	1"
40	55mm	40mm	1 ½"	1 ½"
		45mm		
50	69mm	55mm	2"	2"
65	84mm	70mm	2 ½"	2 ½"
80	103mm	X	3"	3"
100	123mm	100mm	4"	4"
150	190mm	152mm	X	6"

DSP

DN Size	Lug Size (ka)	Hose Tail Size (mm)	BSP Male	BSP Female
40	55mm	38mm	1 ½"	1 ½"
		45mm	2"	2"
65	84mm	70mm	2"	2"
			2 ½"	2 ½"
100	123mm	X	4"	4"