



Flow Meters

Our easy to read WRAS approved flow meters have a large dial to show litres and cubic metres used. Pulsed 10 litres per pulse for remote reading if required they are available in a variety of threads and finishes.

FEATURES:

- EEC Class B approved.
- Working Bar Pressure: 16 Bar.
- Dry Dial.
- For Cold (30 ° C) or warm (90 ° C) Water.
- Brass Body - Available with a variety of inlet and outlet connecting problems.
- Powder epoxy coated.
- Protected rollers.
- Sensitivity index.
- Performances exceed EEC and ISO standards.
- Suitable for horizontal or vertical installation.
- Security via tamper evident wire lock and seal.

TECHNICAL INFORMATION:

DN Size	2" (DN50)
Max Flow	30 m ³ /h
Nominal Flow	15 m ³ /h
Transitional Flow	1050 l/h
Minimum Flow	300 l/h

SIZE: 300mm (l) x 135mm (w)
x 190mm (h)

WEIGHT: 6kg

EEC Approved Class: the EEC classification system used to measure accuracy at very flow rates. Standard ISO 4064 / BSS5728/EEC Specification Class B applies.

OPTIONS:

WM50200BM -	Standard 2 ½" male BSP thread each end - brass
WM50250ILA -	Standard 2" male BSP thread each end - brass
WM50250IGM -	Light Alloy 64mm instantaneous male & female
WM50250CAMLA -	Light Alloy 64mm Camlock male and female
WM5025CAMBR -	Brass 64mm Camlock male & female

Other options available on request.