

## Plain Jet Branchpipes and Nozzles

Our plain jet branchpipe and diffuser nozzles are suitable for up to 16 bar working pressure. Options are available for a single light weight alloy 1 piece combined branch pipe and a 2 piece branchpipe for use in conjunction with screw on plain jet and diffuser nozzles.

### 1 PIECE COMBINED BRANCHPIPE


A lightweight uncontrolled Branchpipe.



<b>MATERIALS:</b>	Light Alloy
<b>INLETS:</b>	2 ½" Male Instantaneous (BS336)
<b>OUTLET:</b>	5/8"
<b>FLOW RATE / 7 BAR:</b>	56 l/min
<b>MAX WORKING PRESSURE:</b>	16 Bar
<b>WEIGHT:</b>	0.7kg

### 2 PIECE BRANCHPIPE WITH SCREW IN NOZZLE

Designed for use in conjunction with screw on nozzle options.



<b>MATERIALS:</b>	Light Alloy
<b>INLETS:</b>	2 ½" Male Instantaneous (BS336)
<b>OUTLET:</b>	2 ¾" Male BSP thread with sealing washer
<b>FLOW RATE / 7 BAR:</b>	57 l/min
<b>MAX WORKING PRESSURE:</b>	16 Bar
<b>WEIGHT:</b>	0.7kg

### PLAIN JET NOZZLE



**OUTLET:** 1 ¾" Female BSP Inlet (with hexagon)  
**SIZES:** 10mm, 13mm, 20mm and 25mm outlet  
**WEIGHT:** 0.2kg



### SCREW IN NOZZLE

**OUTLET:** 1 ¾" Female BSP Inlet (with hexagon). Complete with protective bumper ring. Twist control offers users the option of Jet / Spray and shut off output.  
**MAX WORKING PRESSURE:** 16 Bar  
**WEIGHT:** 0.7kg