

## Standard Breechings

Our standard breechings are available in both dividing & collecting formations. Dividing breechings are used to split a single inlet hose line into two outlets. Collecting breechings are used to combine two hose inlet lines into one outlet. Available in light alloy, gun metal or anodised aluminium.



### DIVIDING BREECHING

Dividing breechings are used to split a single hose line into two. Single inlet with two outlets as standard.

**MATERIALS:** Light Alloy  
Gun Metal  
Anodised Aluminium

**INLET:** 1 x 2 ½" Male Instantaneous (BS336),  
BSP, Storz

**OUTLET:** 2 x 2 ½" Female Instantaneous (BS336),  
BSP, Storz

*Other International connection types available on request.*

**MAX WORKING PRESSURE:** 16 Bar



### COLLECTING BREECHING

Collecting breechings are used to combine two hose lines into one. Two inlets with a single outlet as standard.

**MATERIALS:** Light Alloy  
Gun Metal  
Anodised Aluminium

**INLET:** 2 x 2 ½" Male Instantaneous (BS336),  
BSP, Storz

**OUTLET:** 1 x 2 ½" Female Instantaneous (BS336),  
BSP, Storz

*Other International connection types available on request.*

**MAX WORKING PRESSURE:** 16 Bar